



SFAZ Series Cross-Scored Forward Acting Metal Rupture Disks

Features

- A Fail-Safe Design. If the disk is damaged or incorrectly installed, it will always burst at or below the marked burst rating as indicated on the disk tag
- Designed for Non-fragmentation
- Operating ratios up to 90% of the low end of burst tolerance
- Disk design offers high cycle life
- Excellent for liquid, gas or 2 phased flow
- Standard manufacturing design range and total tolerance ensures marked rating on disk tag does not exceed the MAWP of equipment
- Withstands full vacuum without vacuum support
- Wide range of standard and exotic materials available
- Sizes from 1/2" (13 mm) through 24" (610 mm)
- Burst ratings from 15 psig (1 barg) to 3600 psig (248.28 barg)
- Resists product build-up. The smooth concave side of the disk is exposed to the process media
- 3-dimensional stainless steel tag permanently engraved with complete disk specifications
- ASME UD, CE (PED), and TÜV compliance available



UHZ Disk Holder

Options


SFAZ-L* A process side **PFA Teflon liner** provides protection from corrosive media.

SFAZ-BI* Equipped with ZOOK's Integral **Burst Indicator**

*Note: The maximum temperature rating of rupture disks supplied with liners and BI's is lower than the base disk material.

Safety Relief Valve Protection

When a disk is mounted under a Safety Relief Valve, the working components of the valve are isolated from hostile environments.



SFAZ Series Specifications

Minimum and Maximum Pressure Ratings - psig (barg) @ 72°F (22°C)

Disk Size	Minimum Burst Pressure						SFAZ-L	SFAZ-BI	Maximum Burst Pressure	MNFA in ² (mm ²)	
	316	Inconel	Monel	Nickel	Hastelloy C276						
1/2"	200	200	200	200	300	Same as minimum material	Same as minimum material	3600	0.30		
13 mm	13.79	13.79	13.79	13.79	20.68			248.28	193		
3/4"	150	125	125	125	225			3600	0.53		
19 mm	10.34	8.62	8.62	8.62	15.51			248.28	341		
1"	110	110	100	79	165			3600	0.86		
25 mm	7.59	7.59	6.90	5.45	11.38			248.28	554		
1-1/2"	80	85	73	73	125			3600	2.04		
40 mm	5.52	5.86	5.03	5.03	8.62			248.28	1,316		
2"	61	70	65	61	102			3600	3.36		
50 mm	4.21	4.82	4.48	4.21	7.03			248.28	2,167		
2 1/2"	60	60	60	45	87			2159	4.79		
65 mm	4.14	4.14	4.14	3.10	6.00			148.90	3,090		
3"	60	60	60	45	87			2159	7.39		
80 mm	4.14	4.14	4.14	3.10	6.00			148.90	4,767		
4"	60	60	55	45	84			2159	12.73		
100 mm	4.14	4.14	3.79	3.10	5.79			148.90	8,212		
6"	60	60	55	45	96			1440	28.89		
150 mm	4.14	4.14	3.79	3.10	6.62			99.31	18,638		
8"	60	60	55	45	93			1440	50.03		
200 mm	4.14	4.14	3.79	3.10	6.41			99.31	32,277		
10"	72	72	60	45	111			1440	78.85		
250 mm	4.97	4.97	4.14	3.10	7.66			99.31	50,870		
12"	82	82	65	45	120			720	113.10		
300 mm	5.66	5.66	4.48	3.10	8.28			49.66	72,967		
Max. Temp.	900°F (482°C)	900°F (482°C)*	800°F (427°C)	750°F (399°C)	900°F (482°C)			500°F (260°C)	400°F (204°C)		

Notes: * Contact ZOOK for higher temperatures
 • For materials, sizes, burst ratings and temperatures not shown, contact ZOOK

Teflon liner may be added to provide additional protection against corrosive media

Requirements/Limitations when liner is added:

1. A protective ring is recommended
2. Max. Temperature of 500°F (260°C) – Limitations of liner material
3. Liner may be applied to all ratings. Contact ZOOK if liner is required on both sides of rupture disk
4. The maximum temperature rating of rupture disks supplied with liners and BI's is lower than the base disk material

Manufacturing Design Range & Total Performance Tolerance

ASME						PED				
Burst Pressure (psig)		Manufacturing Design Range			Burst Tolerance	Burst Pressure (barg)		Total Performance Tolerance		
Minimum	Maximum	Good	Better	Best		Minimum	Maximum	Good	Better	Best
1.0	<2.5	-10%	-5%	-0%	±0.33 psig	0.069	<0.172	±50%	-	±0.023 barg
2.5	<5.0	-10%	-5%	-0%	±0.5 psig	0.172	<0.345	±30%	±25%	±0.035 barg
5.0	<7.0	-10%	-5%	-0%	±0.5 psig	0.345	<0.483	±20%	±17.5%	±0.035 barg
7.0	<11.0	-10%	-5%	-0%	±0.8 psig	0.483	<0.759	±20%	±15%	±0.055 barg
11.0	<15	-10%	-5%	-0%	±1.3 psig	0.759	<1.034	±20%	±15%	±0.090 barg
15.0	<26	-10%	-5%	-0%	±2.0 psig	1.034	<1.793	±20%	±15%	±0.138 barg
26.0	<40	-10%	-5%	-0%	±2.0 psig	1.793	<2.758	±15%	±12.5%	±0.138 barg
40.0	Max	-10%	-5%	-0%	±5%	2.758	Max	±10%	±7.5%	±5%

Note: Burst tolerances are the maximum expected variation from the disk's marked burst pressure

Certified Flow Resistance Factors

Krl (Liquid)	Krg (Gas)
1.78	0.39

Teflon - TM The Chemours Company
 Inconel - TM Special Metals Corporation
 Monel - TM Special Metals Corporation
 Hastelloy - TM Haynes International



SFAZ_072019

Visit us at www.zookdisk.com

SERVING AMERICA, CENTRAL & SOUTH AMERICA

16809 Park Circle Drive
 Chagrin Falls, Ohio 44022
 United States

Toll Free: +1 800 543 1043
 Phone: +1 440 543 1010
 Fax: +1 440 543 4930
 E-mail: sales@zookdisk.com

SERVING EUROPE, MIDDLE EAST & AFRICA

Navigation House, Bridge St.
 Killamarsh, Sheffield, S21 1AL
 United Kingdom

Phone: +44 (0) 1909 560999
 Fax: +44 (0) 1909 560860
 E-mail: sales.europe@zookdisk.com

SERVING CANADA

4400 South Service Road
 Burlington, Ontario, L7L 5R8
 Canada

Toll Free: +1 800 370 6057
 Phone: +1 905 681 2885
 Fax: +1 905 681 8838
 E-mail: sales.canada@zookdisk.com

SERVING ASIA PACIFIC

Unit No. 23A-05, Menara Landmark
 No.12, Jalan Ngee Heng
 80000 Johor Bahru, Johor,
 Malaysia

Phone: +60 (7) 2910099
 Fax: +60 (7) 2910096
 E-mail: sales.asia@zookdisk.com



Safety through knowledge and performance.